


	REVISIONS			
REV	DESCRIPTION	DATE	INITIAL	APPROVED
Α	NEW ISSUE	2019-06-03		VM

YT	ASSY QTY	B/O	Part #	UNIT	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	LIFTING EYE	A36PO	3/8 × 2-7/8 × 6-3/4	3
			· -3	3	CONNECTOR ROD	1018	Ø2 X 17	4
			-5	3	BUTTON	BRONZE	Ø2 X 1	5
			-7	3	CONNECTOR HOOK	A36PO	5/8 X 5-1/2 X 5-3/4	6
			-9	3	STOP DISK	A36PO	1/4 X 2 X 2	7
	X		-11	1	WELDMENT			8
	1		-13		MAIN TUBE	CARBON STEEL	3 X 3 X 3/16 WALL X 30-1/4	9
	1		-15		CROSS TUBE	CARBON STEEL	3 X 3 X 3/16 WALL X 23-1/2	10
	2		-17		GUSSET	A36PO	1/4 X 6-1/2 X 3-1/4	11
	3		-19		TUBE CAP	A36PO	1/8 X 3 X 3	
	1		-21		MOUNT PLATE	A36PO	1/4 X 3-1/4 X 10-1/2	13
	2		-23		PIVOT PLATE	A36PO	3/16 X 3-1/2 X 10-1/2	14
	1		-25		ROD	1018	Ø7/8 x 4-3/4	15
	3		-27		PIVOT TUBE	1018	Ø2-1/2 X 3-1/2	16
		B/O	-31	1	GRIP	PVC	FLANGED Ø7/8 MCMASTER-CARR #97045K23	1
		В/О	-33	3	CASTLE NUT	STEL	M16 X 2 MCMASTER-CARR #93760A328	1
		В/О	-35	3	FLAT WASHER	STEEL	M16 MCMASTER-CARR #91166A310	1
		B/O	-37	3	PLUG	PLASTIC	PLUG MCMASTER-CARR #4491K26	1
		В/О	-39	3	BALL LOCK PIN	STAINLESS STEEL	1/4 X 2 MCMASTER-CARR #92384A038	1
		В/О	-41	3	PIN	STEEL	5/8 X 2 MCMASTER-CARR #97245A455	1
		В/О	-43	1	PIN	STEEL	5/8 X 1-1/4 MCMASTER-CARR #98306A491	1
		В/О	-45	1	PIN	STEEL	1/2 X 1-13/32 MCMASTER-CARR #93890A473	1
		В/О	-47	1	DOUBLE LOOP CLIP	STEEL	G.L. HUYETT #BPD-0118	1
		В/О	-49	2	LANYARD	S.S.	6" LOOP/LOOP MCMASTER-CARR #90312A150	1
		B/O	-51	3	LANYARD	S.S.	18" LOOP/LOOP MCMASTER-CARR #90312A360	1
		B/O	-53	9	SPLIT RING	STEEL	7/8 MCMASTER-CARR #90177A217	1
		В/О	-55	7	COTTER PIN	STEEL	1/8 X 1-1/2 MCMASTER-CARR #98338A190	1
		В/О	-57	3	COTTER PIN	STEEL	1/8 X 2 MCMASTER-CARR #98338A200	1
		В/О	-59	2	LABEL	VINYL	SIGNS NOW	17
		В/О	-61	1	RED BARN PLACARD	ALUMINUM	RB41009	18
		В/О	-63	4	#2 DRIVE SCREW	COATED STEEL		1



RED BARN MACHINE

SLING, M/R HEAD 5 BLADE

DWG NO. RBE332A91-3191-00

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON:
DECIMALS
.XXX ± .005 FRACTIONS ± 1/32
.XX ± .01 ANGLES ±.5° DRAWN BY: GILBERT APPROVED \

UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES


.015 x 45° PR .015 R


2. DIMENSIONAL LIMITS APPLY AFTER PLATING


SPEC USED ON MODEL

DATE 2011-04-21 SCALE 1:16

EUROCOPTER SHEET 2 OF 19







DATE

2019-06-03

INITIAL APPROVED

VM

NOTE: .03 DEEP GROOVE AS SHOWN, THIS SIDE ONLY , TO BE INKED AFTER POWDER COAT.

RED BARN MACHINE TITLE SLING, M/R HEAD 5 BLADE DWG NO. RBE332A91-3191-00-1 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 FRACTIONS ± 1/32 DRAWN BY: GILBERT APPROVED HEAT TREAT FINISH POWDER COAT YELLOW ANGLES ±.5° FED #13538 UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES


.015 x 45° PR .015 R


2. DIMENSIONAL LIMITS APPLY AFTER PLATING USED ON MODEL **EUROCPTER** SCALE DATE 1:2 2011-04-21 SHEET 3 OF 19


(-1) TINIC EV


LIFTING EYE

	REVISIONS			
REV	DESCRIPTION	DATE	INITIAL	APPROVED
A	NEW ISSUE	2019-06-03		VM









UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS .XXX ± .005 FRACTIONS ± 1/32 .XX ± .01 ANGLES ±.5° XX ± .1

TITLE

DWG NO.

SCALE

POWDER COAT YELLOW FED #13538 USED ON MODEL **EUROCOPTER**

DRAWN BY: GILBERT

CONNECTOR ROD

UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES

.015 x 45° PR .015 R

2. DIMENSIONAL LIMITS APPLY AFTER PLATING

1:4

DATE 2011-04-21

APPROVED


RED BARN MACHINE

SLING, M/R HEAD 5 BLADE

RBE332A91-3191-00-3


SHEET 4 OF 19

		REVISIONS			
I	REV	DESCRIPTION	DATE	INITIAL	APPROVED
	А	NEW ISSUE	2019-06-03		VM









SECTION B-B





BUTTON

	RB	REI	DBA	۱RN	MA	4C	H۱۱	١E
TITLE		٧G,	M/F	R HE	AD	5 E	3L/	1 D
DWG NO								

	REVISIONS			
REV	DESCRIPTION	DATE	INITIAL	APPROVED
А	NEW ISSUE	2019-06-03		VM







CONNECTOR HOOK

RED BARN MACHINE

SLING, M/R HEAD 5 BLADE

DWG NO. RBE332A91-3191-00-7 DRAWN BY: GILBERT

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON:
DECIMALS
.XXX ± .005
FRACTIONS ± 1/32

FRACTIONS ± 1/32 ANGLES ±.5° .XX ± .01 .X ± .1

UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES
.015 x 45° PR .015 R

2. DIMENSIONAL LIMITS APPLY AFTER PLATING

TREAT
FINISH POWDER COAT YELLOW FED #13538 USED ON MODEL EUROCOPTER

APPROVED


SCALE 2011-04-21 1:3


SHEET 6 OF 19

A

	REVISIONS			
REV	DESCRIPTION	DATE	INITIAL	APPROVED
Α	NEW ISSUE	2019-06-03		VM







STOP DISK

	RED BARN MACHINE
TITLE	SLING, M/R HEAD 5 BLADE
DWG NO	RBE332A91-3191-00-9


UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON: DECIMALS.


JECIMALS TOLERANCES ON: DECIMALS TOLERANCES ON: DECIMAL DRAWN BY: GILBERT APPROVED D Weil HEAT TREAT FINISH POWDER COAT YELLOW FED #13538


REV

USED ON MODEL


EUROCOPTER DATE 2011-04-21 SCALE 1:2 SHEET 7 OF 19









	REVISIONS			
REV	DESCRIPTION	DATE	INITIAL	APPROVED
А	NEW ISSUE	2019-06-03		VM







GUSSET

RED BARN MACHINE

SLING, M/R HEAD 5 BLADE

DWG NO. RBE332A91-3191-00-17

DRAWN BY: GILBERT APPROVED

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON:
DECIMALS
.XXX ± .005 FRACTIONS ± 1/32
.XX ± .01 ANGLES ±.5°

UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES
.015 x 45° PR .015 R
2. DIMENSIONAL LIMITS APPLY AFTER PLATING

USED ON MODEL

SCALE DATE 2011-04-21


EUROCOPTER **SHEET 11 OF 19**

REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine. DESCRIPTION DATE INITIAL APPROVED NEW ISSUE 2019-06-03 2.75 **- 2.75 ---**® RED BARN MACHINE SLING, M/R HEAD 5 BLADE DWG NO. RBE332A91-3191-00-19 UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON:
DECIMALS
.XXX ± .005
.XX ± .01
.X ± .01
.X ± .11
ANGLES ± .5° TUBE CAP DRAWN BY: GILBERT APPROVED SPEC UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES

.015 x 45° PR .015 R

2. DIMENSIONAL LIMITS APPLY AFTER PLATING USED ON MODEL **EUROCOPTER** DATE 2011-04-21 SCALE **SHEET 12 OF 19**



This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine. REV DESCRIPTION INITIAL APPROVED DATE NEW ISSUE 2019-06-03 4.19 -.070 -.510 .17 3.31 1.748 1.70 1.00 Ø.16 5.09 2X .38 10.19 SEE NOTE $\emptyset.635$ NOTE: .03 DEEP GROOVE AS SHOWN, THIS SIDE ONLY, TO BE INKED AFTER POWDER COAT. GROOVE 1 OF 2 NEEDED PER ASSY. RED BARN MACHINE SLING, M/R HEAD 5 BLADE (-23) DWG NO. RBE332A91-3191-00-23 UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON:
DECIMALS
.XXX ± .005
XX + .005
FRACTIONS ± 1/32 DRAWN BY: GILBERT PIVOT PLATE APPROVED ANGLES ±.5° UNLESS OTHERWISE SPECIFIED

1. BREAK ALL SHARP EDGES


.015 x 45° PR .015 R


2. DIMENSIONAL LIMITS APPLY AFTER PLATING USED ON MODEL **EUROCOPTER** SCALE

2011-04-21

SHEET 14 OF 19

1:4





	REVISIONS			
REV	DESCRIPTION	DATE	INITIAL	APPROVED
A	NEW ISSUE	2019-06-03		VM

2019-06-19

.30

C - RBE332A91-3191-00 25

NOTE: BLACK LETTERS, ADHESIVE BACK, ARIAL FONT



LABEL

	RB		R	E	C	E	3,4	\F	1	1	N	V/	4(C	+	I١	1	E
TITLE		••		_						_		_			_			_

SLING, M/R HEAD 5 BLADE


Α

RBE332A91-3191-00-59 UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON:
DECIMALS
.XXX ± .005
.XXX ± .005
.XX ± .01
.XX ± .11
.XX ± .11
.XX ± .11 DRAWN BY: GILBERT APPROVED D Weil

UNLESS OTHERWISE SPECIFIED 1. BREAK ALL SHARP EDGES
.015 x 45° PR .015 R
2. DIMENSIONAL LIMITS APPLY AFTER PLATING

USED ON MODEL EUROCOPTER DATE 2011-04-21 SHEET 17 OF 19 1:1

	REVISIONS			
REV	DESCRIPTION	DATE	INITIAL	APPROVED
Α	NEW ISSUE	2019-06-03		VM




NOTE: ENGRAVE AS SHOWN

	RB	RED	BA	RN	MAC	CHINE		
TITLE	SLIN	۱G, ۱	M/R	HE	AD 5	BLADE		
RBE332A91-3191-00-61							REV	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES				DRAWN BY: GILBERT				
	ANCES C		NINCHE	-5	APPROVED	DW	cil	
DECIMALS .XXX ± .005 FRACTIONS ± 1/32 .XX ± .01 ANGLES ±.5°				4100	HEAT TREAT			
				FINISH				
UNLESS OTHERWISE SPECIFIED				SPEC				
1. BREAK ALL SHARP EDGES					USED ON MODEL			
.015 x 45° PR .015 R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING				EUROCOPTER				
SCALE	1:	:1	DATE	2011	-04-21	SHEET 18	OF 19	

	REVISIONS		done of the	
REV	DESCRIPTION	DATE	INITIAL	APPROVED
Α	NEW ISSUE	2019-06-03		VM

FIRST ARTICLE WEIGHT TEST



INSPECTION & TESTING PROCEDURES FOR THE RBE332A91-3191-00, SLING, M/R HEAD 5 BLADE. THIS ASSEMBLY IS DESIGNED EXCLUSIVELY FOR HOISTING AND INSTALLING/REMOVING THE 5-BLADED MAIN ROTOR HEAD. THIS ASSEMBLY SHOULD BE INSPECTED BEFORE EACH USE. REPLACE ANY ITEMS THAT ARE DAMAGED OR SUSPECTED OF DAMAGE BEFORE USING!

FIRST ARTICLE WEIGHT TEST

- 1. AFTER INSPECTION, PLACE SLING ASSEMBLY ON A OVERHEAD LIFTING DEVICE. ATTACH 3 CONNECTOR HOOKS TO AN APPROAITE TEST WEIGHT OF 5845 LBS, USE BALL LOCK PINS TO LOCK INTO FIXTURE.
- 2. LIFT WEIGHT FOR AT LEAST 5 MINUTES, CONTINUALLY CHECKING FOR CRACKS, DEFLECTION, OR DISTORTION.
- 3. REMOVE WEIGHT AND RE-INSPECT SLING, CHECKING FOR STRESS CRACKS, BENDING, OR DISTORTIONS.

INSPECTOR	* 1
TESTER	
S.N	
DATE	

	RB	RED BARN MACHINE	
TITLE		SLING, M/R HEAD 5 BLADE	
DWG NO.		RBE332A91-3191-00	REV A